

Oils for ATI generators

SPECIFICATIONS

ATI offers the highest quality, industry standard oil reagents for use with TDA series aerosol generators. The reagents are used for in-situ leak testing and production quality control efficiency testing of high efficiency air filters.

PAO-4 (EMERY 3004)

CAS ID 68037-01-4

Name : Poly-alpha-olefin

Specifications:

Boiling point: >316 C Density:
0.819 @ 15.5 C
Vapour pressure: <0.013 kPa at 20
Viscosity: 18 cSt at 40 C/ 4 cSt at
100 C

References : **ATI-ACC-0429** **2 litres of PAO oil**
 ATI-ACC-0430 **20 litres of PAO oil**

Solubility in water: insoluble Appearance/Odour:
colourless, odourless liquid Flash point: 222 C
Auto-ignition point: 343 C



DEHS

CASE ID 122-62-3

Name: Di-2-Ethylhexyl-Sebacat

Specifications:

Boiling point: >212 C Density:
0.9 @ 20 C
Vapour pressure: <0.01 hPa at 20

References : **ATI-ACC-0437** **3 litres of DEHS oil**
 TOP-CON-0001 **1 litre DEHS oil TOP-**
 CON-0002 **5 litres DEHS oil TOP-CON-**
 0003 **20 litres DEHS oil**

Solubility in water: insoluble Appearance/Odour:
colourless and odourless liquid Flash point: 210 C